



GRANOBOND

Strong Bond Beyond Expectations!

GRANOBOND INDUSTRIES LLP

ISO 9001:2015 CERTIFIED COMPANY



COMPREHENSIVE RANGE OF TILING AND GROUTING SOLUTIONS





ABOUT US

A FUTURISTIC BRAND CONCEIVED AND NURTURED WITH THE EXPERIENCE OF 20 YEARS IN CHEMICAL INDUSTRY

GRANOBOND INDUSTRIES LLP

is an Indian brand that manufactures adhesives, sealants, repairs, waterproofing, maintenance & building products and Industrial chemical products which are formulated with world class German polymers & technology. It has developed a comprehensive product range based on Indian & international standards to facilitate construction chemical and building materials market. The brains behind the product development have a combined experience of more than 20 years in the Industrial Chemical industry. With this abundance of experience, the company is ready to build better!

GRANOBOND

Strong Bond Beyond Expectations!

OUR VISION

**THE STRONG
AND PERFECT
TILE SOLUTIONS
FOR A PERFECT
HOME**



:-: GRANOBOND TILE ADHESIVES :-:

A STRONG AND BETTER SOLUTION FOR BEAUTIFUL HOMES



STRENGTH

The high-quality premium adhesives come with high tensile adhesion strength and outstanding non-slip properties which prevents the tiles from slipping, ensuring ultimate strength.

It's easier to get a uniform pattern while working with the tiles. All thanks to the **GRANOBOND** Adhesives Tile

ECONOMY

The applicability of **GRANOBOND** adhesives of tile over larger areas ensures economy and less costs. It's also easier to adjust the tiles after laying which reduces the recurring cost of buying new tiles every time a tile is laid incorrectly.

QUALITY

The premium quality of tile adhesives **GRANOBOND** guarantees outstanding results and excellent applicability for a longer period as they have high bond strength setting quality. and fast



Fast
Setting



High Bond
Strength



High Tensile
Adhesion Strength



Saves Time;
Surface ready to
use within 24 hours

GRANOBOND BRONZE



POLYMER MODIFIED NORMAL TILE ADHESIVE


Cementitious Polymer modified adhesive with No Vertical Slip, suitable for fixing Ceramic and Vitrified Tiles for floor and wall internal application.

CHARACTERISTIC

- 👉 For Ceramic Tiles
- 👉 Grouting on the wall only after 8 hour
- 👉 Application up to 10mm
- 👉 Adjustable
- 👉 Excellent workability
- 👉 No vertical slip
- 👉 Economical & Easy to use
on cement and cement-lime plasters,
cement screeds, cement ground coats,
concrete Surface

Color	: Grey
Pack Size	: 20 kg bag
Mixing Proportion	: 4-4.4 L of water (20-22% by weight) or 20 kg bag
Achieved Thickness	: Up to 10 mm
Compliance/Standard	: C1 T / Type 1
Application Temperature	: Form +5 Deg C to +35 Deg C
Shelf Life	: Unit 12 months since the date of production when stored in undamaged dry conditions and original packaging.

GRANOBOND SILVER



TILE ADHESIVE FOR CERAMIC & VITRIFIED TILES

High Polymer modified grey cement based adhesive with no vertical slip, suitable for fixing ceramic and vitrified tiles for floors and walls in internal application

CHARACTERISTIC

- 👉 For Ceramic and vitrified Tiles
- 👉 No Vertical Slip
- 👉 Up to 10 mm
- 👉 Prolonged workability
- 👉 Adjustable
- 👉 Excellent Workability
- 👉 Application tile on tile application on the floor

Color : Grey & White
Achieved thickness : Up to 10 mm
Packaging : C2 T / Type 1
Coverage : 20 Kg bag

Shelf Life

: As a guide : 1.2kg/m²,/mm of thickness
(Consumption may vary depending on the evenness on the substrate, trowel notch size type of tiles and the application technique.)
: Unit 12 months since the date of production when stored in undamaged dry conditions and original packaging.

SCOPE OF USE

- 👉 GranoBond Silver is a tile adhesive designed for vitrified tiles and ceramic tiles (glazed, terracotta)
- 👉 Indoor uses
- 👉 On horizontal and vertical surfaces
- 👉 On Cement and cement-line plaster, cement screeds, cement ground coats and concrete

GRANOBOND GOLD



POLYMER MODIFIED IMPROVED TILE ADHESIVE

Cementitious, polymer fiber modified tile adhesive with no vertical slip with extended performance. Suitable for fixing ceramic & vitrified tiles for floor & walls in internal & external application.

CHARACTERISTIC

- ➡ Perfect Adherence
- ➡ Allows installation of tiles from top to towards the bottom
- ➡ Can be used for tile on tile application
- ➡ No Vertical Slip
- ➡ Application up to 10 mm
- ➡ Easily trowel able
- ➡ Extended open time

SCOPE OF USE

- ➡ GranoBond Gold is a tile adhesive designed for vitrified tiles and ceramic tiles (glazed, terracotta)
- ➡ Indoor uses
- ➡ On horizontal and vertical surfaces
- ➡ On Cement and cement-line plaster, cement screeds, cement ground coats and concrete

Color	: Grey & White
Achieved thickness	: Up to 10 mm
Packaging	: C2 TE/Type 3
Coverage	: 20 Kg bag
	: As a guide : 1.2kg/m ² ,/mm of thickness (Consumption may vary depending on the evenness on the substrate, trowel notch size type of tiles and the application technique.)
Shelf Life	: Unit 12 months since the date of production when stored in undamaged dry conditions and original packaging.








GRANOBOND DIAMOND







POLYMER MODIFIED TILE & STONE ADHESIVE

Universal Polymer modified, Thin bed and middle bed adhesive for application of ceramic tiles, vitrified tiles and natural stone on wall & floor in internal and external application.

CHARACTERISTIC

-  For ceramic, vitrified (semi and fully) tiles, glass mosaic and natural stone (non-sensitive)
-  On balconies, terraces, wet rooms and bathrooms
-  On water proof and moisture proof layers
-  For inside and outside use
-  Longer open time for safer application
-  Application up to 12 mm
-  For Tile on Tile Application

SCOPE OF USE

-  GranoBond Diamond adhesive mortar for laying ceramic tile, vitrified (semi and Fully) tiles and natural stone (nonsensitive & color fast)
-  Indoors and Outdoors.
-  mortars can be used in rooms exposed to water.
-  It is recommended for floors with elevated functional loads, in shopping malls, staircase.

Color	: Grey & White
Achieved thickness	: Can Be Used Up to 12 mm
Packaging	: C2TES1/Type 3
Coverage	: 20 Kg bag
	: As a guide : 1.2kg/m ² ,/mm of thickness (Consumption may vary depending on the evenness on the substrate, trowel notch size type of tiles and the application technique.)
Shelf Life	: Unit 12 months since the date of production when stored in undamaged dry conditions and original packaging.

GRANOBOND 2K EPOXY GROUT



Two component chemical-resistant epoxy mortar/grout for installation and grouting of tiles, mosaics and stones, where hygiene is of utmost importance such as bathrooms, kitchens, living room, bedroom, hospitals, laboratories, food & beverages industries, dairy industries, swimming pools, showrooms, airports and high traffic areas. It is chemical resistant joint filler. and is available in 24 colors

CHARACTERISTIC

- Indoor and Outdoor Use
- Optimized UV and weather resistant
- Stable and uniform colors for all types of tiles/stones.
- Easy application and cleaning as cementitious grout mortar
- Excellent chemical resistant
- High mechanical strength
- Non Toxic, Anti-bacterial & Anti-Fungal
- Strong, Durable
- Ideal for waterproof grouting
- Vertical resistance/Slip resistant
- Can be used as a grout mortar and adhesive
- Joint width 1 to 12 mm
- Suitable for the contact with food
- Available in 24 colors

SCOPE OF USE

Suitable for chemical-resistant installation and grouting of floor and wall tiles and mosaic in interiors and exteriors with grout joints between 1 and 12 mm wide, such as: (1) Floor and wall tiles, stones in general for residential, public and industrial areas (2) Floor and wall tiles, stones in bathrooms, showers, swimming pool, tanks, thermal or brackish water, spas and hammams (3) Underfloor heating, Kitchen countertops, Terraces and balconies (4) Suited for drinking water and food processing applications.

Packaging	: 1 kg Combo Pack (A+B) 0.900 kg 0.010 kg 5 kg Combo Pack (A+B) 4.500 kg 0.500 kg
Color	: 24 Colors
Consumption formula	: $(A+B) \times C \times D \times 1.70 = \text{kg/m}^2$ (AxB) A = Tile Length (mm) B = Tile Width (mm) C = Tile Thickness (mm) D = Tile Joint (mm)
Shelf life	: Until 12 months in original packaging in dry place

GRANOBOND 3K PREMIUM EPOXY GROUT



Three component chemical-resistant epoxy mortar/grout for installation and grouting of tiles, mosaics and stones, where hygiene is of utmost importance such as bathrooms, kitchens, living room, bedroom, hospitals, laboratories, food & beverages industries, dairy industries, swimming pools, showrooms, airports and high traffic areas. It is chemical resistant joint filler. and is available in 24 colors

CHARACTERISTIC


- ➡ Stain Free
- ➡ Indoor and Covered Outdoor Use
- ➡ Weather Resistant
- ➡ Stable and uniform and cleaning
- ➡ Tiles/Stones
- ➡ Easy application and cleaning as
- ➡ Excellent chemical resistant
- ➡ High mechanical strenght
- ➡ Non-cracking or powdering
- ➡ Non-Toxic, Anti-Bacterial & Anti-Fugal
- ➡ Stong, Durable
- ➡ Ideal for waterproof grouting
- ➡ Vertical resistance/Slip resistant
- ➡ Vertical Resistance/Slip Resistance
- ➡ Joint width 1 to 12 mm
- ➡ Suitable for the contact with food
- ➡ Available in 24 colors

SCOPE OF USE

Suitable for chemical-resistant installation and grouting of floor and wall tiles and mosaic in interiors and covered exteriors with grout joints between 1 and 12 mm wide, such as: (1) Floor and wall tiles, stones in general for residential, public and industrial areas (2) Floor and wall tiles, stones in bathrooms, showers, swimming pool, tanks, thermal or brackish water, spas and hammams (3) Underfloor heating, Kitchen countertops, Terraces and balconies (4) Suited for drinking water and food processing applications.







	Part A 3.5 kg	Part B 1 kg	Part C 0.5 kg
Packaging	: 1/5 kg Pack (A+B+C)		
Color	: 24 Colors		
Mixing Density	: 1.58 g/ml		
Consumption formula	: $\frac{(A+B) \times C \times D \times 1.58}{(A \times B)} = \text{kg/m}^2$		
	A = Tile Length(mm) B = Tile Width(mm) C = Tile Thickness(mm) D = Tile Joint(mm)		
Shelf Life	: Until 24 months in original packaging in dry place		

GLITTERS FOR GRANOBOND 3K EPOXY GROUT



GRANOBOND (Glitters) are specially designed to be used as an additive and metalized effect and enhance the beauty of tiling area. It should be mixed with epoxy-based tile grout to get sparkling joints. It is recommended to use in internal & external areas under wet & dry conditions on wall & floor.

CHARACTERISTIC


-  Mix Easily
-  Permanent Shine
-  Eco Friendly
-  Stain Free
-  Water Resistant
-  Excellent Chemical Resistance




AREA OF USE

All types of ceramic tile, glazed tiles, porcelain tiles, vitrified & fully vitrified tiles, natural stones, large format tiles, glass mosaic tiles, composites & engineered stone.

			
Color	: Copper	Silver	Gold
Recommended Dosage	: 50 gm in 1 kg of GRANOBOND 3K Epoxy Grout (4-6% of weight of GRANOBOND EPOXY GROUT)		
Shelf life	: Best Before 24 Months from the month of packing : if stored properly in undamaged original sealed packaging in dry and cooled conditions.		



GRANOBOND CEMENTIOUS GROUT



GRANOBOND CEMENTIOUS GROUT is a polymer based unsanded cement grout. It is a fine high quality grout mortar for tile and stone joints of 1 to 6 mm width on wall and floor.

CHARACTERISTIC

- ➡ Reduced Water Absorption
- ➡ Abrasion Resistance
- ➡ Ideally Smooth Easy to Apply
- ➡ Extremely Durable Colors
- ➡ Long Working Time
- ➡ Weather Resistance
- ➡ Non Cracking, Non Shrink
- ➡ Suitable For Interior and Exterior Use
- ➡ For Tile Stone Joints

SCOPE OF USE

The addition of **GRANOBOND GROUT ADMIX** to cement base **GRANOBOND CEMENTIOUS GROUT** will enhance adhesion to tile/stone edges, water resistance, improved flexibility and reduces the water permeability of the grout. Mix 200 ml of mix until we get the lump free smooth paste.

WATER-POWDER RATIO : 300-340 ml. water for 1 kg of GRANOBOND CEMENTIOUS GROUT COLORS 24 Colors .

PACKAGING : 1 kg Pouch

CONSUMPTION FORMULS :

$$\frac{(A+B)}{(A \times B)} \times C \times D \times 1.58 = \text{kg/m}^2$$

A = Tile Length(mm) B = Tile Width(mm)
C = Tile Thickness(mm) D = Tile Joint(mm)

SHELF LIFE :

Until 12 Months in Original Packaging and Dry Conditions.



GRANOBOND ADMIX 200 ML FOR CEMENTIOUS GROUTS



GRANOBOND ADMIX 200 ml is a synthetic polymer emulsion additive to use with cement based grout such as granobond Cementious for tile/stone joints grouting works. It improves the adhesive strength to tiles/stones, abrasion resistance, flexibility and reduces the water permeability of the cement grout

CHARACTERISTIC

- 👉 Suitable for Interior & Exterior
- 👉 Improves flexibility and Durability
- 👉 improves the adhesion strength
- 👉 Increase the abrasion resistant of grout
- 👉 Reduced Water permeability
- 👉 Color Fast
- 👉 Improves Water Resistant
- 👉 Easy Application and Cleaning
- 👉 Suitable for submerged conditons



DOGAGE

GRANOBOND ADMIX 200 ML for 1 kg of **GRANOBOND** cementious grout

APPERANCE	: White Liquid
PACKAGING	: 200 ml Bottle
Ph	: > 8
RECOMMENDED TILE JOINT WIDTH	: 1-6 mm
SHELE LIFE	: Until 12 Months in Original Packaging and Dry Condition (Bigger Packing sizes are available on request)
SHELE LIRE	: Until 15 Months since the date of productions when stored in undamaged dry conditions and original packaging.



GRANOBOND TILE & STONE CLEANER



GRANOBOND TILE & STONE CLEANER is powerful, fast acting, heavy duty Hydrochloric based cleaner for regular cleaning of dirt and stains on tile surfaces, designed for daily maintenance of tiles. It may also be used as general purpose cleaner on other acid resistant surface. It is designed for removal of cement residues, efflorescence and most oxide stains.

CHARACTERISTIC

- ➡ Ready to Use
- ➡ Fast Acting
- ➡ Easy to Apply and Use
- ➡ Remove cement film
- ➡ Removes, residues, efflorescence and most oxide stains
- ➡ For Interior & Exterior cleaning applications of Tiles surface floor and wall

SCOPE OF USE

- ➡ All Unglazed Ceramic Tile
- ➡ Glazed Ceramic Tile
- ➡ Glass Tile
- ➡ Vitrified Tile
- ➡ Glass Mosaic Tile
- ➡ Porcelain Tile
- ➡ Quarry (Pre-wet surface prior to application to reduce absorption)
- ➡ Terracotta (Pre-wet surface prior to application to reduce absorption)
- ➡ Stone (Pre-wet surface prior to application to reduce absorption)

For Stone Cleaning : (Recommended dilution with water - 1:10-1:15)

(Note : not all stones can handle acid cleaning, so always check the stone type before using any acid-based cleaner)

Color : Light Yellow

Packaging : 1 Ltr

Appearance : Liquid

Coverage : Coverage depends on the porosity of surface and intensity of stains on the surface.

Shelf Life : 12 Months (In original unopened container.)

Store in dry conditions between 5°C and 30°C, Protect from direct sunlight



GRANOBOND 2K & 3K EPOXY GROUT


Coverage Chart*

Joint Width in mm	Tile Size (Lenght * Breadth * Thickness in mm)									
	100 x 100 x 3	150 x 150 x 4	200 x 150 x 5	150 x 300 x 6	300 x 300 x 6	450 x 300 x 7	600 x 450 x 8	600 x 600 x 8	600 x 900 x 11	900 x 900 x 12
2	4.38	4.93	4.51	4.38	6.57	6.76	8.45	9.86	8.61	9.8
3	2.92	3.28	3.00	2.92	4.38	4.51	5.63	6.57	5.74	6.57
4	2.19	2.46	2.25	2.19	3.28	3.38	4.22	4.93	4.30	4.93
6	1.46	1.64	1.50	1.46	2.19	2.25	2.81	3.28	2.87	3.28
8	1.09	1.23	1.12	1.09	1.64	1.69	2.11	2.46	2.15	2.46
10	0.87	0.98	0.9	0.87	1.31	1.35	1.69	1.97	1.72	1.97
12	0.73	0.82	0.87	0.73	1.09	1.12	1.40	1.64	1.43	1.64


Epoxy Grout & Cementious Grout Colors



TILE LEVELING SPACER



GRANOBOND INDUSTRIES LLP



Manufactured & Marketed by :

GRANOBOND INDUSTRIES LLP
REGD. OFFICE & CORP.OFFICE

TS-1007 10th Floor, Plot no-C-03 Galaxy
Blue Sapphire Plaza, Sector-4 Greater Noida
(Gautam Buddha Nagar) 201305

Uttar Pradesh, India

Customer Care No.: 8448470095

info@granobond.com / www.granobond.com

Follow Us :

